



Gulf Supreme Duty ULE

Premium heavy duty diesel engine oil for Ultra low emission engines

Product Description

Gulf Super Duty ULE is premium performance heavy duty diesel engine oil specially developed for use in ultra low emission engines meeting the latest US and European emission standards. This oil addresses the unique needs of the latest engines and enhances the life of exhaust after treatment devices. It is formulated with state-of-the-art additive technology and severely hydroprocessed base oils to provide excellent performance and overall protection having a potential to offer extended drain intervals. It meets the performance requirements of API CK-4 service category. It is also backward compatible for the use in older engines requiring API CJ-4 and below quality oils.

Features & Benefits

- Outstanding thermal and oxidative stability reduces low-temperature sludge build-up, high-temperature deposits and oil thickening
- Excellent soot handling capability minimises soot related viscosity increase and leads to longer engine/oil life
- Superior shear stability maintains viscosity in severe service conditions and leads to improved wear protection.
- Exceptional TBN retention resists harmful effects of corrosive exhaust gases and extends oil life
- Low ash content reduces particulate build-up in Diesel Particulate Filter (DPF) and enhances its life.

Applications

- Latest high performance low emission heavy duty diesel engines including those equipped with DPF and Exhaust Gas Recirculation (EGR) and meeting the latest US and European emission standards.
- On-highway vehicles and off-highway equipment operating in severe low speed/heavy load conditions using either low (500 ppm) or ultra low (15 ppm) sulphur fuels.
- Suitable for the use in earlier engine models requiring API CJ-4 and below quality oils.

Specifications, Approvals & Typical Properties

Has the following Approval		10W-30	15W-40
API CK-4		X	X
Typical Properties			
Test Parameters	ASTM Method	Typical Values	
Viscosity @ 100 °C, cSt	D 445	12.0	15.6
Viscosity Index	D 2270	143	133
Flash Point, °C	D 92	230	230
Pour Point, °C	D 97	-33	-30
Density @ 15°C, Kg/l	D 1298	0.887	0.862
Phosphorus, %wt	D 4927	0.11	0.11
Sulphated Ash, %wt	D 874	1.0	0.96

March 2017

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com